

ALUMINUM SHELL HOIST



It adopts Class E insulation, 100% pure copper wire wrap, aluminum metal shell, free from iron metal shell defects. Aluminum metal case It has fast heat dissipation, which greatly enhances the working efficiency and service life of the motor. The gear is heat treated and processed with high precision It has unique wear resistance, each gear is supported by bearings, strong and efficient, and the strength is generally several times that of the teeth. gearbox High-grade new bearings are selected inside, which has long bearing life, low resistance and low transmission sound.

Product model	CD-K1 300-600	CD-K1 300-600	CD-K1 350-700	CD-K1 350-700	CD-K1 500-	CD-K1 500-	CD-K1 600-1200	CD-K1 600-1200	CD-K1 700-1500
How to use	Single rope	Single rope	Single rope	Single rope	Single rope	Single rope	Single rope	Single rope	Single rope
	Double rope	Double rope	Double rope	Double rope	Double rope	Double rope	Double rope	Double rope	Double rope
Rated voltage	380V 50HZ	220V 50HZ	380V 50HZ	220V 50HZ	380V 50HZ	220V 50HZ	380V 50HZ	220V 50HZ	220V 50HZ
Power (KW)	1.7	3	2.2	3	2.2	2.2	3	3	4
Rated lifting capacity (KG)	300	300	350	350	500	500	600	600	750
	600	600	700	700	1000	1000	1200	1200	1500
Lifting speed (m/min)	24	28	24	24	14	14	14	14	14
	12	14	12	12	7	7	7	7	7
Lifting height (m)	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100
	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100
Wire rope diameter	5	5	5	5	6	6	6	6.3	7