

# Round Sling Eye & Eye



- Lightweight: Easy to use, with a wide load-bearing surface, it can reduce surface load pressure.
- High strength: Made of filament, it has high strength and elastic recovery.
- Made of High Quality synthetic fibre,
- Reinforced wear-resistant materials.
- Corrosion resistance: The material has good chemical quality and is not afraid of mold or insects.

WLL	Working load limit with 1 webbing sling						Working load limit with 2 webbing sling				Approximate width mm	Minimum length m	maximum length m
	Vertical lifting	Bolted lifting	0°-7°	7°-45°	45°-60°	Up to 45°	Straight up to 45°	Choker up to 45°	Straight 45°-60°	Choker 45°-60°			
WLL 1T	1	0.8	2.0	1.4	1	0.7	1.40	1.12	1.0	0.8	40	1	100
WLL 2T	2	1.6	4.0	2.8	2	1.4	2.80	2.24	2.0	1.6	50	1	100
WLL3T	3	2.4	6.0	4.2	3	2.1	4.20	3.36	3.0	2.4	60	1	100
WLL 4T	4	3.2	8.0	5.6	4	2.8	5.60	4.48	4.0	3.2	70	1	100
WLL 5T	5	4.0	10.0	7.0	5	3.5	7.00	5.60	5.0	4.0	75	1	100
WLL6T	6	4.8	12.0	8.4	6	4.2	8.40	6.72	6.0	4.8	80	1	100
WLL 8T	8	6.4	16.0	11.2	8	5.6	11.20	8.96	8.0	6.4	90	1	100
WLL 10T	10	8.0	20.0	14.0	10	7.0	14.00	11.2	10.0	8.0	100	1	100
WLL 12T	12	9.6	24.0	16.8	12	8.4	16.80	13.44	12.0	9.6	110	1	100
WLL 15T	15	12.0	40.0	28.0	15	14.0	21.00	16.8	15.0	12.0	125	1	100
WLL 20T	20	16.0	60.0	42.0	20	21.0	28.00	22.4	20.0	16.0	150	1	100
WLL 25T	25	20.0	50.0	35.0	25	17.5	35.00	28.0	25.0	20.0	180	1	100
WLL 30T	30	24.0	60.0	42.0	30	21.0	42.00	33.6	30.0	24.0	200	1	100
WLL 40T	40	32.0	80.0	56.0	40	28.0	56.0	48.8	40.0	32.0	200	1	100
WLL 50T	50	40.0	100.0	70.0	50	35.0	70.00	56.0	50.0	40.0	220	1	100
WLL 60T	60	48.0	120.0	84.0	60	42.0	84.00	67.20	60.0	48.0	220	1	100
WLL 80T	80	64.0	160.0	112.0	80	56.0	112.0	89.6	80.0	64.0	260	1	100
WLL100T	100	80.0	200.0	140.0	100	70.0	140.0	112.0	100.0	80.0	290	1	100